

Roll 1410 SEA

01002027-xxx OLI-1



*Photo for illustrative purposes

External dimensions [L x l x h]

1000 x 1200 x 2000 mm

Internal dimensions* [L x l x h]

805 x 1050 x 1580 mm

Internal volume

1420 L

Empty weight

177 Kg

Cold source - advices

Eutectic plate : up to 4 eutectic plates TOP370 toute température selon le référentiel Olivo existant.

Insulated container standard specifications

Box & door :

- **Monobloc wall** in UV-resistant food-grade polyethylene ;
- Injected polyurethane foam ;
- **Monobloc EPDM frame seal** ;
- **Sealed lateral Pelican® closure**, yellow zinc coating, ergonomic handling sheath, 2 locking points, and 1 galvanized door stop ;
- **270° door opening** ;
- **Double-axis zinc-plated box-door hinge** ;
- **2 side-handling handles** rotationally molded into the mass ;
- **Stainless steel drain plug for water drainage** and special rotomolded bottom for water retention.

Logistical specifications : ISO pallet 1200 x 1000

Chassis :

- **Embedded support frame** with yellow zinc coating ;
- **9 metal feet**, diameter 80 mm ;

Accessory options

Intermediate grid : up to 2 steel grids with polyamide coating or stainless steel ;

Customization

Signage : heat-sealed adhesive – ready-to-print file provided by the client.

Tracking : temperature/GPS tracking solution.

Branding marking : engraved aluminum plate 150 x 90 mm

* Average value for reference purposes



Chilled



Frozen



Ambient



Thermal

Insulated container properties

Coef K.	0.33 W/m2.°C
ATP category	IR
Temperature resistance	-80°C/+70°C
Double wall thickness	≈ 100 mm
Internal convection grooves	

Mechanical

Static load capacity - Kg

Double-walled, rotational-molded and grooved

Update 26/10/2023

